

SCHEDULE A (page 1 of 2)

□ 101 Consumers Drive, 2nd Floor, Whitby (905)723-3818
 □ 181 Perry Street, 2nd Floor, Port Perry (905) 985-4889

Test Pit Open: ☐ Yes ☐ No Date: ____ By: _____ Water Supply: Site Inspection: ☐ Proposed ☐ Existing Soil Profile (m) Soil Classification: ☐ Municipal ☐ Dug/Bored ☐ Drilled Est. Perc. Rate min/cm ☐ Other ____ Sieve Analysis: ☐ Yes ☐ No High Water Table Level ____ (below grade) Class of System ☐ 1, 2 or 3 ☐ 4 ☐ 5 ☐ Install Repair Alter Number of Fixture Units Daily Sewage Flow (DSF) Type **Number of Fixtures** # of Bedrooms _____ living space ____ ____ x 4.0 = Water Closet (toilet) Bathtub or Shower _____ x 1.5 = _____ Washbasin ____ x 1.5 = ____ 1. Base Flow from # of bedrooms _____ (max 2500 L) ____ x 1.5 = Laundry Tub 2. Additional Flow based on dwelling size: (each 10 $\rm m^2$ or part there of, 100 L over 200 to 400 $\rm m^2$, 75L for 400 to 600 $\rm m^2$, 50L for > 600 $\rm m^2$) Clothes Washer ____ x 1.5 = ____ Dishwasher Kitchen Sink ____ x 1.5 = __ ___ x 1.5 = ____ Bathroom Group ____ x 6.0 = 3. Additional flow based on fixture units: 50L per each unit over 20: Other _____ 4. Additional flow for each bedroom over 5 (500 L)_____ Total = ____ Total: 1 plus greater of 2, 3 or 4 = **Dosed Systems:** Tank(s): Size of Pump Chamber - _____ L Litres per dose _____ L Septic Tank Size (residential) DSF x 2 = ______proposed _____L Balancing Tank Size - _____L Septic Tank Size (non-residential) DSF x 3 = ______proposed ______L Number of doses per day _____L Size of Dose - _____L Holding Tank Size (residential) Minimum DSF x 7 = _____ proposed _____L Type of Control Panel: Holding Tank Size (non-residential) = minimum 9000 L proposed L Other Treatment Unit = ______L



SCHEDULE A (page 2 of 2)

Type of Leaching Bed:				
□ conventional trench □ filter bed □ type □ in ground □ raised	Percolation rate of fill			
Conventional Trench:				
DSF x T/200 =m Config	jured as	runs of	m =	m
Filter Bed:				
Effective Area = DSF/75 L/m² (≤ 3000 L/day) =	m ² Configured	as m x	m =	m ²
DSF/50 L/m2 (>3000 - 5000 L/day) # Cells	_/50 =m² Confi	igured as m x _	m =	m²
Distribution Pipes: Configured as	runs of	_ m Totalı	m	
Expanded Contact Area = Q x T/850 =	_ x/850 =	m² Configured as	m x m =	m²
Loading Rate: ☐ imported ☐ irregular				
DSF/Loading Rate Factor =	m² configured as	m x	m=	m2
Type A Dispersal Bed				
Stone Area = Q/75 (≤ 3000 L/day) = = Q/50 (> 3000 L/day) =	m² configured as _ m² configured as _	m x m x	m = m =	m²
Dispersal Area (Sand) = QT/850 (T ≤ 15) = _ = QT/400 (T>15) = _	m ² configured a	m x m x	m = m =	m² m²
Distribution Pipes: Configured as	runs of	m	=	m
Type B Dispersal Bed				
Dispersal Area = DSF X T/400 = m ² Or = DSF/ loading rate (using table 2-8 of BCMOH) =				m ²
Linear Loading Rate = DSF/ 40 (where T ≥ 24) = m = DSF/ 50 (where T < 24) = Or				m
From Table 2-11 of BC	MOH =	_ m		
Dispersal Bed Configuration = Distribution Pipes: Configured as	m x runs of	m =	m ² # of Beds m	
Level IV Treatment Unit/Tertiary Treatment Unit				
Manufacturer Model	BMEC/B	NQ Authorization	# Units	
Method of Headerline and Distribution Pipe Detection: magnetic means tracer wire (14 gauge TW solid copper light coloured plastic coated) other means of subsurface detection, please specify				