

	FOOTING		STUD	BOLT	REBAR	
BASE TYPE	DEPTH H	DIA A	DIST B	CIRCLE C	CAGE DIA	ANCHOR TYPE
I	1500	460	171	242	NOT REQUIRED	PRE-SET ANCHOR ASSEMBLY 22mm TYPE DGR-2S
II	2600	610	287	406	508	PRE-SET ANCHOR ASSEMBLY 32mm OPSD 2215.02
III	2600	760	287	406	585	PRE-SET ANCHOR ASSEMBLY 32mm OPSD 2215.02

6. CONCRETE SHALL BE CSA SPECIFICATION C-1 35 MPa CLASS OF EXPOSURE IN ACCORDANCE WITH CSA A23. 1-09 TABLE 1 & 2. ALL DIMENSIONS IN MILLIMETRES EXCEPT WHERE NOTED.

CSA STANDARD W186.

5. REBAR CAGE TO BE WELDED STEEL CONSTRUCTION AND ALL REBAR TO BE GRADE 400. THE WELDING OF REINFORCING STEEL BARS SHALL CONFORM TO



CONCRETE FOOTING FOR BASE MOUNTED LIGHTING AND SIGNAL POLES DWG. DATE: 1980 06 REVISION NO.: 20 REV. DATE: 2021 04 SCALE: N.T.S.

S-400.010