

Part 1 - General

1.01 Description

- .1 This Section specifies requirements for stripping and storing topsoil.

1.02 Related Specification

- .1 Construction Specification Section 01570 – Environmental Protection
- .2 OPSS.MUNI 201 - Construction Specification for Clearing, Close Cut Clearing, Grubbing and Removal of Surface and Piled Boulders
- .3 OPSS.MUNI 206 - Construction Specification for Grading
- .4 OPSS 802.MUNI - Construction Specification for Topsoil
- .5 OPSS 805.MUNI - Construction Specification for Temporary Erosion and Sediment Control Measures

1.03 Basis of Payment

- .1 Payment for stripping and storing topsoil to be included in the unit price bid in the Form of Tender for construction of pipeline.

Part 2 - Products -Not Applicable

Part 3 - Execution

3.01 Stripping Topsoil

- .1 Clear and grub area prior to stripping topsoil.
- .2 Remove topsoil from areas indicated on Contract Drawings or as directed by the Contract Administrator.
- .3 Do not mix topsoil with subsoil or other materials.

3.02 Storing Topsoil

- .1 Stockpile topsoil in areas approved by Contract Administrator.
- .2 Do not place topsoil in or near dripline of tree stands, within three (3) metres of flood plains or regulation limits of local Conservation Authority or

in areas containing natural wildlife habitats.

- .3 Construct perimeter drainage ditches to intercept and divert run-off to adjacent settling ponds.
- .4 Provide temporary erosion control measures in accordance with OPSS.MUNI 805.

END OF SECTION